AL/2019/01/E-I(NEW)				4320
සියලු ම හිමිකම් ඇව්ටිණි / ගු ගු	ரப் பதிப்புரிமையுடை	யது/All Rights Reserved	<i>d</i>]	
	නව නිඊදෙ	<i>கை/புதிய பாடத்திட்</i>	டம்/New Syllabus	
தே வேறு திலை காற்றைக்கும் தினை பாராது காறு குறை குறு குறு குறு குறு குறு குறு குறை குறை குறு குறு குறு குறை குறை குறை குறை குறை குறை குறை	லே இல்லை இல்லு வில்லு வில் வில்லு விலு விலு விலு விலு விலு விலு விலு வி	eres and the second a		තාර්තමේන්තුව ලී ලංකා විභාග ලෙපාර්තමේන්තු කොඩ இலங்கைப் பரீட்சைத் திணைக்கள anka Department of Examinations, Sri Lani පාර්තමේන්තුව ලී ලංකා විභාග දෙපාර්තමේන්තු කොට இலங்கைப் பரீட்சைத் திணைக்கள
අධාන සංඛ Gener	கை சைந்து கள பி பொதுத் தர al Certificate of	ற்கிக் පற் (උසස් எ ாதரப் பத்திர (உயர் Education (Adv. La	පළ) 5லைக, 2 தர)ப் பரீட்சை, evel) Examination	019 අගෝස්තු 2019 ඉ கஸ் ற் , August 2019
භෞතික විදාහාව I பௌதிகவியல் I Physics I				09.08.2019 / 0830 – 1030 ஜா.க දෙකයි இரண்டு மணித்தியாலம் Two hours
Instructions: * This question * Answer all th * Write your In * Read the inst * In each of t which is cor a cross (×) in	paper consists of questions. odex Number in ructions given o the questions 1 rect or most a n accordance wi Use (Consider that t	of 50 questions in 12 the space provided in n the back of the ans to 50, pick one of ppropriate and mark th the instructions give of calculators is not the acceleration due to	pages. a the answer sheet wer sheet carefully the alternatives j your response ven on the back t allowed. gravity a = 102	t. y. from (1), (2), (3), (4), (5) on the answer sheet with of the answer sheet. $1 s^{-2}$
			gravity, $g = 10 \text{ m}$	15-)
. Which of the follo (1) m	(2) I	fundamental unit?	(1) K	(5) mol
The dimensions of (1) $L^2M^{-1}T^{-1}$	f the gravitation (2) L^2M^{-2}	(3) Cu nal constant G are (3) $L^2M^{-2}T^{-1}$	given by (4) $L^3M^{-1}T$	$^{-2}$ (5) $L^{3}M^{-2}T^{-2}$
. When a bipolar jun (1) turn on the th (3) increase the c (5) not change th	ction transistor ransistor. ollector current e collector cur	operates in saturation (2) turn off t . (4) decrease t rent.	n mode, a further the transistor. The collector current	increase in base current will ent.
 According to the (1) 6 quarks. (3) 4 quarks and (5) 6 quarks and 	evidences found 4 leptons. 6 leptons.	d in Particle Physics (2) 6 leptons (4) 6 quarks	and 4 leptons.	posed of
The variation of the	gravitational po	tential $V(r)$ due to a p	oint mass, with di	stance r is best represented b
V(r) V		(r)	$ V(r) \wedge $ $ r 0 \qquad \qquad$	V(r)
Which of the follow	(4) wing statements	(3) is incorrect regard	(4)	(3)
 (1) There must be (2) Mercury-glass (3) By using a mercury can be increased 	e a measurable thermometers ercury-glass the sed.	physical quantity the consist of thin-walle ermometer with a lar	that varies with t ad glass bulbs. ge mercury bulb	emperature. , the range of measuremen
(4) Two different as all thermore	types of thermo netric propertie	meters may give slig s are not equally se	htly different read ensitive.	lings at the same temperatur
(5) Having a large	e contact angle	between mercury an	d glass is an adv	vantage for accurate reading



- 3 -13. Consider the following statements regarding the dew point of air having water vapour in a closed container. (A) At dew point, unsaturated water vapour becomes saturated water vapour. (B) If the temperature is reduced below the dew point, some of the vapour will condense. (C) At dew point, if the volume of the container is reduced, the absolute humidity of the air will decrease. Which of the above statements is/are correct? (1) Only A (2) Only B (3) Only A and B (4) Only A and C (5) All A, B, and C 14. When the tension of a wire is slowly increased from T_1 to T_2 within the proportional limit, its length changes from l_1 to l_2 . The energy stored in the wire during this process is (1) $(T_2 + T_1)(l_2 - l_1)$ (2) $\frac{1}{2}(T_2 - T_1)(l_2 + l_1)$ (3) $\frac{1}{2}(T_2 - T_1)(l_2 - l_1)$ (4) $\frac{1}{2}(T_2 + T_1)(l_2 + l_1)$ (5) $\frac{1}{2}(T_2 + T_1)(l_2 - l_1)$ 15. Hydrogen gas in a container is maintained at standard temperature (300 K) and pressure $(1 \times 10^5 \text{ N m}^{-2})$. If the root mean square speed of hydrogen molecules is 2 km s⁻¹, what is the density of hydrogen in the container? (1) 0.038 kg m^{-3} (2) 0.075 kg m^{-3} (3) 0.150 kg m^{-3} (4) 1.225 kg m^{-3} (5) 2.450 kg m^{-3} 16. A composite rod is formed by connecting two rods A and B as shown in the figure. Longitudinal wave velocities in rods A and B are 3210 m s⁻¹ and 6420 m s⁻¹, respectively. A longitudinal pulse applied at the free end of the rod A propagates with a wavelength of 2m. What is the wavelength of this wave when it propagates through rod B? A B (1) 1 m (2) 2 m(3) 3 m (4) 4 m (5) 5 m 17. The magnitude and the direction of the electric field at point A due to the point charge distribution shown in the figure are (1) $\frac{2q}{4\pi \varepsilon_0 a^2} \rightarrow$ +3a(2) $\frac{q}{4\pi \varepsilon_0 a^2}$ \uparrow (3) $\frac{2q}{4\pi \varepsilon_0 a^2} \leftarrow$ (4) $\frac{6q}{4\pi \varepsilon_0 a^2}$ [†] (5) $\frac{6q}{4\pi \varepsilon_0 a^2} \downarrow$ 18. Three capacitors with equal capacitance and two batteries with equal electromotive force (emf) are given to construct a circuit to store energy. Which of the following circuits stores the maximum energy?

(3)

(4)

AL/2019/01/E-I(NEW)

(1)

(2)

[See page four

(5)



[See page five

- 5 -

4320







30. An ideal gas expands from state A to state C along two different paths, ABC and ADC, as shown in the P-V diagram. The heat absorbed by the gas during the processes AB and BC are 200 J and 700 J, respectively. What is the change in internal energy, when the gas expands along the path ADC?

(1)	380 J	(2)	520	J
(3)	720 J	(4)	880	J
(5)	1080 J			



(3)

E

0

31. A ball is dropped freely to a floor from a height of 1 m. If its speed is reduced by 25% at each bounce, what would be the height the ball reaches after three bounces?

- (1) $\frac{3}{4}$ m (2) $\left(\frac{3}{4}\right)^2$ m (3) $\left(\frac{3}{4}\right)^3$ m (4) $\left(\frac{3}{4}\right)^6$ m (5) $\left(\frac{3}{4}\right)^9$ m
- **32**. Part of an orbiting satellite is coated with a metal that has a work function of 5 eV. The Planck constant is $4 \cdot 1 \times 10^{-15}$ eV s and the speed of light is 3×10^8 m s⁻¹. What could be the longest wavelength of incident sunlight that can eject an electron from the metal coating?
 - (1) 12·3 nm (2) 246 nm (3) 683 nm (4) 800 nm (5) 1230 nm
- 33. A standard photographic slide has a picture size of 30 mm \times 40 mm. An enlarged image of the slide is projected onto a screen 4.0 m away from the projection lens of a 'single-lens slide projector'. If the size of the image on the screen is $1.2 \text{ m} \times 1.6 \text{ m}$, what should be the focal length of the projection lens?

(1) 4.9 cm (2) 9.8 cm (3) 10.2 cm (4) 49 cm (5) 98 cm



[See page eight

37. For optimum operation of a light emitting diode (LED), forward voltage and current should be 2V and 10 mA, respectively. Transistor is having $V_{BE} = 0.7 \text{ V}$, current gain $\beta = 100$, and $V_{CE(sat)} = 0.1$ V. For the circuit shown in the figure, what are the values of R_B and R_C for the optimum operation of the LED?

(1) $R_B = 100 \Omega$ and $R_C = 1 k\Omega$ (2) $R_B = 1 \,\mathrm{k}\Omega$ and $R_C = 1 \,\mathrm{k}\Omega$ (3) $R_B^{P} = 1 \,\mathrm{k}\Omega$ and $R_C^{P} = 290 \,\Omega$ (4) $R_B = 10 \,\mathrm{k}\Omega$ and $R_C^{P} = 1 \,\mathrm{k}\Omega$ (5) $R_B^{P} = 10 \,\mathrm{k}\Omega$ and $R_C^{P} = 290 \,\Omega$

- 38. A piece of metal is attached to the top of a rectangular wooden block that floats in water. As shown in the figure, 50% of the volume of the wooden block is submerged in water. The metal piece and the wooden block have the same mass. If the wooden block with the metal piece is flipped up side down, what could be the percentage of the volume of the wooden block submerged in water?
 - (1) Slightly smaller than 50%
 - (4) Slightly larger than 50%
- (2) Much smaller than 50% (5) Much larger than 50%
- 39. As shown in the figure, an incompressible liquid flows steadily through a horizontal pipe. Two narrow vertical tubes are fixed at two places on the horizontal pipe where the cross-sectional areas are A and 2A. If the height difference of the liquid columns in the two vertical tubes is h, flow rate of the liquid through the pipe is

- 8 -

(1)
$$A\sqrt{2gh}$$
 (2) $A\sqrt{6gh}$
(3) $A\sqrt{\frac{3gh}{2}}$ (4) $2A\sqrt{\frac{gh}{3}}$
(5) $2A\sqrt{\frac{2gh}{3}}$

- 40. The figure shows the displacement-time graphs for the motion of two cars with respect to a lamp post aside the road. Consider the displacement to the right side of the lamp post as positive. A student has made the following statements regarding the motion of cars relevant to the points P, Q, and R marked on the graph.
 - (A) Relevant to P: Car 1 coming from left crosses Car 2.
 - (B) Relevant to Q: Both cars are moving towards the lamp post and cross each other.
 - (C) Relevant to R: Car 2 coming from right passes the lamp post.

Which of the above statements is/are correct?

- (1) Only B
- (4) Only B and C

(2) Only C (5) All A, B, and C





	A whistling firecracker having a co- initially with an acceleration, then v An observer at ground directly belo	onstant whistling f with a deceleration, w the firecracker li	requency is fire and finally bla s stens to the whi	d vertically upward. It travels sts before coming to the rest stling sound of the firecracker
	Consider the following statements r	egarding the frequ	ency of the sour	nd heard by the observer.
	(A) During the acceleration, it	is higher than th	e whistling freq	uency and is decreasing with
	 (B) During the deceleration, in time. (C) Lust before the blast, it before the blast. 	t is lower than th	e whistling free	puency and is increasing with
	(C) Just before the blast, it be Which of the above statements is/an (1) Only A	re correct? (2) Only B	ne whisting he	(3) Only C
	(4) Only A and B	(5) Only B a	and C	
42.	A metal bowl of mass 700 g con water at 27 °C. When a steel ball	ntains 1 litre of of mass 300 g	Metal	Specific Heat Capacity (J kg ⁻¹ K ⁻¹)
	at 120 °C is dropped into the wa	ter in the bowl,	Aluminium	900
	the final temperature of water is	measured to be	Iron	450
	30 °C. Specific heat capacities of ste	el and water are	Copper	385
	$500 \text{ J kg}^{-1} \text{ K}^{-1}$ and $4200 \text{ J kg}^{-1} \text{ K}^{-1}$,	respectively. Out	Silver	230
	of the metals given in the table, w	nat could be the	Lead	128
	(1) Aluminium (2) Copper		Leau	120
	(3) Lead (4) Iron			
	(5) Silver			
	are no gaps between the contact su prisms. A ray entering through the f an incident angle i , refracts at faces and DF and emerges from the face	rfaces of the Face AB with AB, BC, CD, DE without devia	tion. The angles	n_3 E of refraction at the faces AB
	BC, and CD are r_1, r_2 , and r_3 , respect (1) $\sin i = n_1 \sin r_1$ (4) $n_2 \cos r_2 = n_3 \sin r_3$	ctively. Which of the (2) $n_2 \sin r_2 =$ (5) $\cos i = n_2$	the following exp = $n_1 \cos r_1$ $_3 \cos r_3$	(3) $\sin i = n_3 \cos r_3$
44.	BC, and CD are r_1, r_2 , and r_3 , respect (1) $\sin i = n_1 \sin r_1$ (4) $n_2 \cos r_2 = n_3 \sin r_3$ Each of the single turn wire loop current I. A uniform magnetic field each wire loop can rotate freely above choice represents the order of loops	ctively. Which of the (2) $n_2 \sin r_2 =$ (5) $\cos i = n_2$ (5) $\sin i = n_2$ (6) $\sin i = n_2$ (7) $\sin i = n_2$	the following exp = $n_1 \cos r_1$ $_3 \cos r_3$ blane as shown e positive direct xis perpendicula rque acting on the	in figures, carries the same ion of the x-axis. Assume that r to the magnetic field. Which them are in descending order
44.	and <i>DD</i> , and energes from the face <i>BC</i> , and <i>CD</i> are r_1, r_2 , and r_3 , respect (1) $\sin i = n_1 \sin r_1$ (4) $n_2 \cos r_2 = n_3 \sin r_3$ Each of the single turn wire loop current <i>I</i> . A uniform magnetic field each wire loop can rotate freely above choice represents the order of loops <i>y</i> (<i>P</i>) <i>y</i> (ctively. Which of the (2) $n_2 \sin r_2 =$ (5) $\cos i = n$ (5) $\cos i = n$ (5) $\cos i = n$ (5) $\cos i = n$ (5) $\sin i = n$ (6) $\sin i = n$ (7) $\sin i = n$ (8) $\sin i = n$ (9) $\sin i$	the following exp = $n_1 \cos r_1$ $_3 \cos r_3$ blane as shown the positive direct xis perpendicula rque acting on the (R)	in figures, carries the same ion of the x-axis. Assume that r to the magnetic field. Which them are in descending order $y \bigwedge_{\substack{5\\5\\4\\4}} (S)$
44.	and <i>DD</i> , and enlerges from the face <i>BC</i> , and <i>CD</i> are r_1, r_2 , and r_3 , respect (1) $\sin i = n_1 \sin r_1$ (4) $n_2 \cos r_2 = n_3 \sin r_3$ Each of the single turn wire loop current <i>I</i> . A uniform magnetic field each wire loop can rotate freely above choice represents the order of loops y (P) y (P) y (I)	ctively. Which of the (2) $n_2 \sin r_2 =$ (5) $\cos i = n$ as placed on xy placed on xy placed on xy placed along the put its symmetric as that the initial to (2) y (3) 4 x 0	the following exp = $n_1 \cos r_1$ $_3 \cos r_3$ plane as shown the positive direct xis perpendicular rque acting on the (R) (R)	in figures, carries the same ion of the x-axis. Assume that r to the magnetic field. Which them are in descending order $y \wedge (S)$
44.	and <i>DD</i> , and energes from the face <i>BC</i> , and <i>CD</i> are r_1, r_2 , and r_3 , respect (1) $\sin i = n_1 \sin r_1$ (4) $n_2 \cos r_2 = n_3 \sin r_3$ Each of the single turn wire loop current <i>I</i> . A uniform magnetic field each wire loop can rotate freely above choice represents the order of loops <i>y</i> (<i>P</i>) <i>y</i> (<i>P</i>) <i>y</i> (<i>P</i>) <i>y</i> (<i>P</i>) <i>y</i> (<i>Q</i>) <i>y</i> (<i>P</i>) <i>y</i> (<i>Q</i>) <i>y</i>	ctively. Which of the (2) $n_2 \sin r_2 =$ (5) $\cos i = n$ (5) $\cos i = n$ (5) $\cos i = n$ (5) $\cos i = n$ (3) Q, P, R, S	the following exp = $n_1 \cos r_1$ $_3 \cos r_3$ blane as shown the positive direct xis perpendicular rque acting on the (R) (R) (4) S, R, Q	in figures, carries the same ion of the x-axis. Assume that r to the magnetic field. Which them are in descending order $y \bigwedge (S)$
44.	and <i>DD</i> , and energes from the face <i>BC</i> , and <i>CD</i> are r_1, r_2 , and r_3 , respect (1) $\sin i = n_1 \sin r_1$ (4) $n_2 \cos r_2 = n_3 \sin r_3$ Each of the single turn wire loop current <i>I</i> . A uniform magnetic field each wire loop can rotate freely above choice represents the order of loops y (P) y (P) y (G) y (P) y (G) y (G) y (I) P,Q,R,S	ctively. Which of the (2) $n_2 \sin r_2 =$ (5) $\cos i = n$ (5) $\cos i = n$ (5) $\cos i = n$ (5) $\cos i = n$ (3) Q, P, R, S	the following exp = $n_1 \cos r_1$ $_3 \cos r_3$ blane as shown the positive direct xis perpendicular rque acting on the (R) (R) (A) (A) S, R, Q	in figures, carries the same ion of the x-axis. Assume that r to the magnetic field. Which them are in descending order $y \bigwedge (S)$

45. Three cells with electromotive force (emf) E_1 , E_2 , and E_3 , and internal resistances r_1 , r_2 , and r_3 , respectively, are connected as shown in the figure. Which of the following expressions gives the potential at point P of the circuit?

(1)
$$\frac{E_1 + E_2 + E_3}{3}$$

(2) $\frac{E_1 E_2 E_3}{E_1 E_2 + E_2 E_3 + E_3 E_1}$
(3) $\frac{E_1 r_1^2 + E_2 r_2^2 + E_3 r_3^2}{r_1 r_2 + r_2 r_3 + r_1 r_3}$
(4) $\frac{E_1 r_2 r_3 + E_2 r_1 r_3 + E_3 r_1 r_2}{r_1 r_2 + r_2 r_3 + r_1 r_3}$

(5)
$$\frac{E_1 r_2 r_3 + E_2 r_1 r_3 + E_3 r_1 r_2}{r_1 r_2 r_3}$$

46. Consider a battery of electromotive force (emf) E_0 and internal resistance r. As shown in the figure, it is connected in series with a resistor R and a variable dc voltage source which can be reversible. When the voltage of the variable source V_{VR} is varied, the graph of I vs V is best represented by







47. Consider the circuit shown in the figure. The graphs show the waveforms of the applied voltage and the current through the load L.



(5) $2V_m I_m$

The average power dissipation of the load is

(2)

(1) 0

$$\frac{I_m I_m}{4}$$

(3) $\frac{V_m}{\sqrt{2}} \frac{I_m}{\sqrt{2}}$ (4) $V_m I_m$

[See page eleven





සියලු ම හිමිකම් ඇව්රිණි/ගුඟුப பதிப்புரிமையுடையது/All Rights Reserved]
ை கிட்குக்குக் பிதிய பாடத்திட்டம்/New Syllabus
ே என். நீவல் என்றின்றே இ குண தல்ல் என்று குறைகளைகளு குறைகள் குறைகள் குறைகள் குறைகள் குறைகள் இலங்கைப் பரி. கூத் இனங்கைப் பரி. காத் திணைக்களம் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களும் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திலை என்று குறைகள் இலங்கைப் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களம் இலங்கைப் பரி. காத் திணைக்களம்
අධායන පොදු සහතික පතු (උසස් පෙළ) විභාගය, 2019 අගෝස්තු
கல்விப் பொதுத் தராதரப் பத்திர (உயர் தர)ப் பரீட்சை, 2019 ஓகஸ்ந்
General Certificate of Education (Adv. Level) Examination, August 2019
භෞතික විදාහාව II
பௌதிகவியல் II (01 ட 13.08.2019 / 0830 – 1140
Physics II
(අලතර කියවීම් කාලය - මිනිත්ත 10 යි
மூன்று மணித்தியாலம்
Three hours Additional Reading Time - 10 minutes
Use additional reading time to go through the question paper select the questions and decide on the questions
that you give priority in answering
that you give priority in answering.

Important:

- * This question paper consists of 16 pages.
- This question paper comprises of two parts, Part A and Part B. The time allotted for both parts is three hours.
- * Use of calculators is not allowed.

PART A — Structured Essay: (pages 2 - 8)

Answer all the questions on this paper itself. Write your answers in the space provided for each question. Note that the space provided is sufficient for your answers and that extensive answers are not expected.

PART B – Essay: (pages 9 - 16)

This part contains six questions, of which, four are to be answered. Use the papers supplied for this purpose.

- * At the end of the time allotted for this paper, tie the two parts together so that Part A is on top of Part B before handing them over to the Supervisor.
- * You are permitted to remove only Part B of the question paper from the Examination Hall.

Index No. :

4320

For Examiners' Use Only

	For the second	paper
Part	Question Nos.	Marks Awarded
	1	
	2	
Α	3	na here l
	4	
	5	Second and
	6	he of the second
	7	and the strength
В	8	l tall-out
	9 (A)	
	9 (B)	
	10 (A)	
	10 (B)	
	In numbers	
Total	In words	
B		

Code Numbers

Marking Examiner 1	
Marking Examiner 2	
Marks checked by	
Supervised by	

[see page two





[see page four

A 1 /2010/01 E 11/NTETXX	4320	
An incomplete diagram of ar metal by the Searle's method	- 4 - a experimental setup to determine the a is shown below.	thermal conductivity of a Do not write in this column
(a) What are the purposes of P:	$\begin{array}{c} T_1 & T_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_2 & \theta_2 \\ \hline \\ \theta_1 & \theta_1 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_1 & \theta_1 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_1 & \theta_1 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_1 & \theta_1 \\ \hline \\ \theta_1 & \theta_2 \\ \hline \\ \theta_1 & \theta_1 \\ \hline \\ \theta_1 & \theta$	eam generator?
(b) Proper connections of st obtain the accurate result(i) Steam supply (A or	eam and water supply to Searle's ap Accordingly, select each connection B) :	pparatus are necessary to and give reasons.
Reason:		
(ii) Water supply (L or Reason:	<i>M</i>) :	
(c) State three more measur specific measurement tak	ing instruments needed in this experimen by each of them.	ment and briefly state the
Instrument	Measurement	
(i)		
(iii)		
(iii)		
(d) The separation between the readings of T_1 and T_2 and gradient.	the thermometers T_1 and T_2 is 8.0 cm. If re 73.8 °C and 59.2 °C, respectively,	f the constant temperature calculate the temperature

see page five

AL/2019/01-E-II(INE W)	AL	/20	19/0	1-E-	II(C	NEW
------------------------	----	-----	------	------	------	-----

		 	_

(e)	Does this temperature gradient vary along the rod? Briefly explain the answer.	Do not write
		column
(f)	At thermal steady state, the difference in thermometer readings of T_3 and T_4 is 9.5 °C and the flow rate of water is 120 g per minute. Calculate the rate of heat absorption by water. (Specific heat capacity of water is 4200 J kg ⁻¹ K ⁻¹ .)	
(g)	If the cross-sectional area of the rod is 12.0 cm ² , calculate the thermal conductivity of the metal and state the answer with SI unit.	
(<i>h</i>)	Is it possible to use the Searle's method to find thermal conductivity of a poor conductor? Briefly explain the answer.	\bigcirc
		\bigcirc
3. A st the (<i>a</i>)	tandard spectrometer, a glass prism, and a monochromatic light source are used to determine refractive index of the glass. A few necessary adjustments are to be done to the spectrometer before starting to take measurements.	
	(i) What is the adjustment that should be done to the eyepiece?	
	(ii) Telescope is pointed to a distant object and it is adjusted until a clear image of the object is formed on the cross wires. What is the purpose of this adjustment?	
	(iii) What is the adjustment that should be done to the slit of the collimator?	
	(iv) The telescope is brought in line with the collimator. Then the collimator is adjusted until a sharp image of the slit is formed on the cross wires. What is the purpose of this adjustment?	

AL /2019/01-E-II(NEW)

L/ 4 0	19/01-E-II(NEW) - 8 -	-
(e)	With the given potentiometer, the balance length can be measured with a maximum error of 1 mm. If $R = 8 \Omega$, $l_0 = 72.4 \text{ cm}$ and $l = 50.1 \text{ cm}$, calculate the maximum value that could be obtained for the internal resistance r .	Do n write in th colu
(ƒ)	Internal resistance r can be determined more accurately by a graphical method. Considering R as a variable resistor, rearrange the equation obtained in (d) to plot a suitable graph. Write down the independent (x) and dependent (y) variables of the graph.	
	x :	
(g)	The potentiometer circuit shown in figure (1) can be modified by replacing the part of the circuit marked X in figure (1), by the circuit shown in figure (2). For this, the terminals S' and T' of the circuit shown in figure (2) are connected respectively to points S and T of the potentiometer circuit shown in figure (1).	
	 (i) Assume that the balance point is located between A and B in the modified circuit. What is the colour of the Light Emitting Diode (LED) which is lit when the sliding key is placed at A and B? 	
	At A :	
	(ii) Briefly explain how the balance point could be found using the modified circuit.	
	•••••••••••••••••••••••••••••••••••••••	
	(iii) State two advantages of this modified circuit in finding the balance point, when compared with the circuit shown in figure (1).	
		1
	* *	
		1.

[see page nine

- 9 -



Assume all the joints in this device are free to move without friction. During the rotation, flyballs move horizontally and it makes the sleeve move up and down along the rotating axle. This device is symmetric about the rotating axle. Opening and closing of the throttle valve is automatically controlled by the rotational speed of the turbine. All the other parts of the device can be assumed to be massless except the flyballs.

- (i) Draw the free body force diagram for a flyball assuming each arm connected to it, is under tension. Consider the mass of a flyball to be m.
- (ii) If the angular velocity of each flyball about the rotational axle is ω rad s⁻¹, show that the tensions in the upper and lower arms are respectively given by $\frac{ml}{2}\left(\omega^2 + \frac{g}{h}\right)$ and $\frac{ml}{2}\left(\omega^2 - \frac{g}{h}\right)$.

Here l is the length of each arm and h is the height to each flyball from the lower clamp.

- (iii) When the frequency of the output voltage is 50 Hz, the value of h is 30 cm. Show that the contribution to the tension from the term $\frac{g}{h}$ can be neglected.
- (iv) If m = 1 kg and l = 50 cm, calculate the tension in an upper arm.
- (v) When the frequency of the output voltage is 50 Hz, the contraction of the spring is 20 cm. Determine the spring constant of the spring.
- (c) When the frequency of the output voltage is 50 Hz, the throttle valve is set to block 50% of the flow. That is, the valve is making an angle of 45° with the axis of the flow tube as shown in figure (2). Assume that the closing of the throttle valve is proportional to the angle of the valve with the axis of the tube.



The frequency of the output voltage depends on the consumption of electricity. When the consumption increases, the output frequency decreases and vice versa.

- (i) According to the design, when the frequency of the output voltage becomes 25 Hz, the throttle valve will be fully opened. The valve will remain fully open even for frequencies lower than 25 Hz. Determine the following at the instant of fully opening the throttle valve. (Neglect the
 - contribution from the term $\frac{g}{h}$)
 - (1) Tension of an upper arm
 - (2) Contraction of the spring
- (ii) When the frequency of the output voltage increases, the throttle valve closes gradually to decrease the flow rate. If the flow is to be blocked by 75%, what should be the frequency of the output voltage?
- 6. (a)(i) Draw the standing wave patterns of the fundamental mode and the first two overtones produced by a vibrating stretched string, in three separate diagrams. Mark the nodes as 'N' and the antinodes as 'A' in the diagrams. (Neglect end corrections.)
 - (ii) Obtain an expression for the frequency f_n of the n^{th} harmonic in terms of n, T, l, and m, where T is the tension, l is the length, and m is the mass per unit length of the string.
 - (iii) For a given string, state two possible ways of changing the harmonic frequencies.
 - (b) A harp like musical instrument shown in figure (1) consists of 7 identical stretched strings with different lengths. The longest string of length l_{1} , produces the musical note 'C' (∞ , ∞) with the fundamental frequency of 260 Hz. The corresponding lengths of the strings which produce all the musical notes are given in the table as fractions of l_1 .

Musical Notes	ස	8	ග	۱	ප	ධ	නි
	C	D	Е	F	G	A	В
	സ	ரி	க	Ш	Ц	த	நி
$\frac{l}{l_1}$	1.00	0.89	0.79	0.70	0.67	0.59	0.53



(i) If all the strings are under the same tension, calculate the fundamental frequencies of musical notes 'F'(O, \square) and 'B' (S, \square).

(ii) To obtain a correct musical note, the frequency can be fine tuned by adjusting the tension of the string. By what percentage should the tension of the string be adjusted to change the frequency by 1%?

- (c) A student designs and builds a set of panpipes to produce musical notes given in the above table, by using narrow PVC pipes with different lengths as shown in figure (2). Lower end of all the pipes are closed with corks.
 - (i) Draw the standing wave patterns of the fundamental mode and the first two overtones produced by a one end closed pipe of length L, in **three** separate diagrams. Mark the nodes as 'N' and the antinodes as 'A' in the diagram. (Neglect end corrections.)



- (iii) The longest pipe is found to be producing a frequency of 255 Hz instead of 260 Hz. By what distance should the cork be moved to obtain the frequency of 260 Hz.
- (iv) If the cork fell completely out of a pipe, what would happen to the fundamental frequency produced by the pipe? Justify the answer with a suitable diagram.
- 7. When an object is falling through a viscous medium, it is subjected to the buoyant force and the drag force. The buoyant force pushes the object upward while the drag force acts against the motion of the object with respect to the medium.
 - (a) The drag force for a solid spherical object falling in a liquid medium can be expressed by the Stokes' Law.
 - (i) Write down the Stokes' formula for a solid spherical object and name the parameters.
 - (ii) Write down two assumptions that are used in deriving the Stokes' formula.
 - (b) Consider an air bubble rising gradually upward in a viscous fluid. Stokes' Law can be applied to determine the time taken by an air bubble to reach the surface of the fluid. Neglecting the effect of the pressure change with height, the instantaneous velocity V(t) of an air bubble in a viscous medium at a given time t can be given by

 $V(t) = V_T \left(1 - e^{-\frac{\tau}{\tau}} \right)$, where V_T and τ are the terminal velocity and the relaxation time of the motion

of the air bubble, respectively.

- (i) If the relaxation time for the motion of an air bubble in a viscous medium is $4 \mu s$, calculate the time it takes for the instantaneous velocity to be 50% of V_T from the rest (Take $\ln 0.5 = -0.7$)
- (ii) Calculate the time taken by the air bubble to increase the instantaneous velocity from 50% to 90% of V_{T} . (Take $\ln 0.1 = -2.3$)
- (iii) Considering the answers obtained in (b)(i) and (b)(i) above, plot the variation of the instantaneous velocity of the air bubble as a function of time. Clearly indicate V_r on the graph.
- (c) Consider an air bubble rising from the bottom of an oil tank which is filled upto 10 m height.
 - (i) Obtain an expression for the resultant force acting on the air bubble in terms of η , ρ_o , ρ_a , a, and v, where η is the coefficient of viscosity of oil, ρ_o is the density of the oil, ρ_a is the density of air, a is the radius of the air bubble, and v is the velocity of the air bubble.
 - (ii) It is given that $\eta = 7.5 \times 10^{-2}$ Pa s, $\rho_0 = 900$ kg m⁻³, $\rho_a = 1.225$ kg m⁻³, and the average radius of an air bubble a = 0.1 mm. Neglecting the weight of the air bubble, and the effect due to the variation of pressure with height, calculate the terminal velocity of the air bubble.
 - (iii) Calculate the radius of the air bubble just below the surface of the oil, if the internal pressure of the bubble is 100.33 kPa, atmospheric pressure is 100 kPa, and the surface tension of oil is 2.0×10^{-2} N m⁻¹.
 - (iv) Considering the change in radius of the air bubble with height, sketch the variation of its instantaneous velocity with time.





If the radius of the path of the electron beam is r, obtain an expression

for the ratio $\left(\frac{e}{m}\right)$ of the electron.

see page thirteen

Circular coils

Figure (4)

- (34 PM IIT 31 III 01 III 1
- (c) A dc voltage can be applied between two parallel metal plates P and Q as shown in figure (3). The plates P and Q are separated by a distance d as shown in figure (4). While the magnetic field B is applied, the potential difference between the plates V_{PQ} can be adjusted until there is no deflection of the electron beam. This process can be utilized as an alternative way to determine the speed of the electrons.
 - (i) Draw the electric and magnetic forces acting on an electron within the plates P and Q, after the above adjustment is done.
 - (ii) Obtain an expression for the speed of the electrons in terms of d, B and V_{PQ} .
 - (iii) When B = 1 mT and $V_{PQ} = 0$, the radius of the path of the electrons is 6 cm. When $V_{PQ} = 840$ V, there is no deflection of the electron beam. The separation between the plates P and Q is 8 cm. Calculate
 - (1) the speed of an electron, and

(2) the charge to mass ratio $\left(\frac{e}{m_e}\right)$ of an electron.

9. Answer either part (A) or part (B) only.

Part (A)

- (a) The electromotive force (emf) of an electric source is defined as the work done by the source on a unit charge. Using this definition;
 - (i) determine the units of emf.
 - (ii) obtain an expression for the power generated by a source in terms of its emf E and the current I flowing through it.
 - here S_1 S_1 S_1 S_1 S_2 M S_2 M Car Battery E $r = 0.03 \Omega$ Figure (1)
- (b) A source of emf E and internal resistance r is connected to an external resistor with resistance R. Obtain an expression for the total energy dissipated in the circuit in time t, in terms of E, r, R, and t.
- (c) Consider an electrochemical battery of a car that powers the starter motor and the headlamps as shown in the circuit of figure (1). Rated power of each headlamp is 60 W. The internal resistance of the battery is 0.03 Ω . Consider that the ammeter behaves as an ideal ammeter.

When only the headlamps are turned on $(S_1 \text{ is closed})$ without starting the car $(S_2 \text{ is open})$, the voltmeter shows a value of 12.0 V.

- (i) What is the reading of the ammeter?
- (ii) What is the resistance of a headlamp?
- (iii) Calculate the emf of the battery.
- (d) When the starter motor is just turned on $(S_2 \text{ is just closed})$ while the headlamps are ON, the ammeter shows a value of 8.0 A. Calculate,
 - (i) the current through the starter motor, and
 - (ii) the resistance of the starter motor.
- (e) When the armature of the starter motor is rotating while the headlamps are ON, the current through the starter motor is 34.2 A and the voltmeter reading is 11.0 V. Calculate,
 - (i) the back emf, and
 - (ii) the efficiency of the starter motor, at this instant.
- (f) Sketch the variation of the back emf E_b of the motor with the current flowing through it.

- (g) The battery discharged considerably because the driver parked the car without turning off the headlamps on a certain night. As a result, emf of the battery dropped to 10.8 V and its internal resistance increased to $0.24 \ \Omega$. The current through the starter motor was not sufficient to rotate it due to the discharge of the battery. Find the current through the starter motor at this instance.
- (h) In the situation mentioned in (g) above, the driver used an external battery with an emf 12.3 V and an internal resistance 0.02Ω to jump start the car. For this, the external battery was connected to the discharged battery using two jumper cables, each having a resistance of 0.015Ω and the car was then started.
 - (i) Draw the circuit diagram showing the connections to the external battery with the discharged battery, when jump starting the car.
 - (ii) Calculate the maximum current through the starter motor when starting the engine.

Part (B)

- (a) (i) Why Field Effect Transistors (FET) are called unipolar devices? What are the charge carriers contributing to the operation of FETs?
 - (ii) State why FETs are also known as voltage-controlled devices.
 - (iii) Calculate the drain current I_D and the Gate-Source voltage V_{GS} for the circuit shown in figure (1), assuming $V_D = 5$ V.



Figure (1)

(b) In the Op-amp circuit shown in figure (2), each electromechanical switch S_i (i = 0, 1, 2, 3) is operated by applying an electrical signal D_i (i = 0, 1, 2, 3) which can be 'High' (5V) or 'Low' (0V). When D_i is 'High' the respective switch S_i will be closed and otherwise, it will be open.



Figure (2)

- (i) When D_2 is 'High', find the current through the resistor 10R in terms of R.
- (ii) If a set of voltages (5V, 0V, 5V, 5V) is applied simultaneously to operate the switches S_3 , S_2 , S_1 , S_0 , respectively, calculate the current *I* indicated in figure (2) in terms of *R*.
- (iii) Calculate the output voltage V_0 when a set of voltages (5V, 5V, 5V, 5V) is applied simultaneously to operate the switches S_3 , S_2 , S_1 , S_0 , respectively.

(c) A cash operated snack dispenser will provide a pack of 'Marie' or 'Chocolate Cream' biscuits under the following conditions. • The correct amount of cash is inserted (1) 'Marie' (M) or 'Chocolate Cream' (C) is selected If 'Marie' is selected, 'Availability of Marie' in the dispenser (X) If 'Chocolate Cream' is selected, 'Availability of Chocolate Cream' in the dispenser (Y) (i) Obtain the logic expression for the conditions under which a pack of biscuits may be obtained. (ii) Show how this may be implemented using logic gates. 10. Answer either part (A) or part (B) only. Part (A) (a) (i) State the Boyle's law and the Charles' law. (ii) Derive the ideal gas equation using the above laws. (b) A deflated tyre of volume V and initial pressure P_0 , at room temperature T_R is connected to a compressed nitrogen (N₂) gas tank via a valve. The tyre initially contains only N₂ gas. After inflating the tyre with N_2 gas, its final pressure is P and it contains a total of n number of N_2 moles. Assume that there is no change in volume of the tyre. (i) Assuming that the N₂ gas inside the tyre behaves like an ideal gas, show that the number of moles of N₂ gas pumped into the tyre is $n\left(1-\frac{P_0}{P}\right)$. (ii) Obtain an expression for the work done to inflate the tyre with N_2 gas. (iii) Assuming that the pumping process of N_2 gas is adiabatic, show that the change in the temperature of the N₂ gas inside the tyre is $\frac{2}{5}\left(1-\frac{P_0}{P}\right)T_R$. The change in internal energy of an ideal gas is given by $\Delta U = n C_V \Delta T$, where C_V is the molar heat capacity at constant volume and ΔT is the change in temperature. The molar heat capacity at constant volume of a diatomic ideal gas is $\frac{5R}{2}$, where R is the universal gas constant. (iv) This change in temperature, increases the pressure temporarily to a higher value. Show that this change in pressure is $\frac{2}{5}(P-P_0)$. (c) Gauge pressure is the pressure measured relative to atmospheric pressure. Gauge pressure of a tyre is usually expressed in psi (pound per square inch) units. $(1 \text{ atm} \simeq 100 \text{ kPa} \text{ and } 1 \text{ psi} \simeq 7 \text{ kPa})$ A deflated tyre at 20 psi pressure is pumped further with N₂ gas to a pressure of 30 psi at room temperature (27° C). (i) Calculate the change in temperature of N_2 gas in the tyre. (ii) Calculate the maximum pressure in the tyre due to this change in temperature. (iii) Usually this temporary increase in pressure is not observable when pumping N₂ gas further to a deflated tyre. Give two possible reasons for not observing the increase in pressure. Part (B) Read the following passage and answer the questions. Radioactivity is a spontaneous decay process by which an unstable nucleus becomes a stable nucleus by emitting radiation. Decay rate is directly proportional to the number of radioactive atoms present at that instant but independent of external physical conditions. Radioactive iodine ¹³¹I is used in nuclear medicine to treat patients with thyroid cancer. The half-life time of ¹³¹I is 8 days. It decays to stable ¹³¹Xe initially by emitting a β^{-} particle and then by emitting a γ -photon. The maximum tissue penetration length of this β is 2 mm. Usually ¹³¹I is administered to patients as sodium iodide (Na¹³¹I) in the form of a capsule. Once administered, it is absorbed into the blood stream and concentrated in the thyroid gland. Radiation emitted from ¹³¹I kills most of the cancer cells in the thyroid gland.

Since the patient becomes a potential source of radiation, precautions must be taken to minimize the radiation exposure to others around. The amount of radiation emitted by the patient is proportional to the activity of the dose administered. In medical practice, the common unit used for activity is Curie (Ci) which is not an SI unit. One Curie is equal to 37×10^9 disintegrations per second.

A radioactive material inside the body, diminishes not only by radioactive decay but also by biological clearance. This clearance is purely a biological process and follows an exponential variation, characterized by the decay constant λ_b . Hence the effective decay constant λ_e , due to both radioactive decay and biological clearance can be stated as $\lambda_e = \lambda_p + \lambda_b$, where λ_p is the decay constant corresponding to physical radioactive decay. The effective half-life time, which is used for radiation protection measures, is calculated from the effective decay constant.

- (a) (i) State two differences between the emissions of β^{-} and γ .
 - (ii) Rewrite the following decay equation replacing a, b, and c with correct numbers.

 $^{131}_{53}I \longrightarrow ^{131}_{a}Xe + ^{b}_{c}\beta^{-}$

- (b) A fresh sample of Na¹³¹I, having an activity of 100 mCi is received by a hospital. The sample is stored in a lead container at room temperature.
 - (i) What is the SI unit used for activity?
 - (ii) Write down an expression for the decay constant λ in terms of half-life time T.
 - (iii) Calculate the activity of the above sample after 4 days and express the answer in SI units. (Take $\ln 2 = 0.7$ and $e^{-0.35} = 0.7$)
 - (iv) Hence, express the change in activity as a percentage.
 - (v) Is it possible to reduce the activity of the Na¹³¹I sample if it is stored at 0 °C instead of storing at room temperature? Explain the answer.
- (c) A small amount of Na¹³¹I sample having an activity of 100 mCi is administered to a thyroid patient.
 - (i) When dealing with such a patient, for which mode of emission, the radiation protection measures should be taken? Explain the answer.
 - (ii) Show that the effective half-life time T_e of ¹³¹I in thyroid gland can be given by $\frac{1}{T_e} = \frac{1}{T_p} + \frac{1}{T_b}$, where T_p and T_b are the half-life times due to radioactive decay and biological clearance, respectively.
 - (iii) If the biological half-life time of ¹³¹I in thyroid gland is 24 days, calculate the effective half-life time of ¹³¹I (in days).
 - (iv) Calculate the percentage change in the activity after 4 days of administration of 131 I. (Take $e^{-0.46} = 0.63$)
 - (v) According to radiation protection regulations, ¹³¹I treated patients can be discharged from the hospital when the activity is below or equal to 50 mCi. If this regulation is followed, how long the above ¹³¹I treated patient has to be kept in isolation in the hospital before discharging?

* * *